



Hi-Temp Solutions for Industry

Woven Fiberglass Tapes Service to 1000°F (550°C)

Manufactured from continuous filament texturized fiberglass yarns. Woven into a strong and flexible tape. Excellent for protecting various equipment and apparatus from heat. Applications include: Pipe & Hose Wrap, Furnace Door strip curtains, Gaskets, Furnace/Oven Door Seals, Electrical Cable Wrap, Exhaust Wrap, etc. Available in PG (Premium Grade) & IG (Industrial Grade). Available Plain & Drop Warp. All rolls 100 ft length. (Minimums may apply)

| PRODUCT CODE | THICKNESS | WIDTHS | PRODUCT CODE | THICKNESS | WIDTHS |
|--------------|-----------|---------|--------------|-----------|---------|
| IG320 | 1/32" | 1/2"-6" | PG650 | 1/16" | 1/2"-6" |
| IG650 | 1/16" | 1/2"-6" | PG1250 | 1/8" | 1/2"-6" |
| IG1250 | 1/8" | 1/2"-6" | | | |
| IG2500 | 1/4" | 1"-6" | | | |

ABOVE PRODUCTS ARE ALSO AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE.



Vermiculite Coated Fiberglass Tape—Short Term 1500°F (825°C)

Manufactured from continuous filament texturized fiberglass yarns. Woven into a strong and flexible tape with a vermiculite coating which adds higher temperature resistance as well as abrasion resistance. Short term service temperature to 1500°F, intermittent to 2000°F. Also available in black color. Plain & Drop Warp available. (Minimums may apply)

| PRODUCT CODE | THICKNESS | WIDTHS | PRODUCT CODE | THICKNESS | WIDTHS |
|--------------|-----------|---------|--------------|-----------|---------|
| IG320 | 1/32" | 1/2"-6" | PG650 | 1/16" | 1/2"-6" |
| IG650 | 1/16" | 1/2"-6" | PG1250 | 1/8" | 1/2"-6" |
| IG1250 | 1/8" | 1/2"-6" | | | |
| IG2500 | 1/4" | 1"-6" | | | |

ABOVE PRODUCTS ARE ALSO AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE.

Maxsil Silica Tape for 2000°F (1100°C)

Maxsil Silica Tape is manufactured from texturized amorphous silica filament yarn and woven into a strong and flexible form for service temperature to 2000°F continuous. Product is manufactured to exact thicknesses and widths. Continuous filament silica fiber is texturized into a bulky yarn which provides excellent insulating abilities. Improved abrasion and tensile strength over competitive products. Maxsil Silica Tape is not manufactured from leached fiberglass cloths or tapes. Plan & Drop Warp available. (Minimums may apply)

| PRODUCT CODE | THICKNESS | WIDTHS | LENGTH |
|--------------|-----------|--------|--------|
| SPG650 | 1/16" | 1"-4" | 100 FT |
| SPG1250 | 1/8" | 1"-4" | 100 FT |

ABOVE PRODUCTS ARE ALSO AVAILABLE WITH PRESSURE SENSITIVE ADHESIVE.
REFERENCE SPG650-PSA OR SPG1250-PSA.

