



Maxsil® Tex Tadpole Seals for 2000° F  
**Furnace and Oven Door Seals for High Temperature**



# Maxsil® Tex Tadpole Seals for 2000° F



Maxsil® Tex Tadpole Seal  
Style MTS-30-MRB

Maxsil® Tex Tadpole Seals are manufactured from our continuous filament amorphous silica fiber. The yarn is texturized from filament silica fiber along with a high temperature finish added for excellent strength and abrasion resistance. Significantly more durable at high temperatures than standard leached silica fabrics. A replacement for Ceramic Fiber door seals.

**Standard Tadpole Cover:** Style MTS-30  
Also available with Vermiculite Coating for increased durability.

**Standard Tadpole Core:** Style Maxsil® MRB Rope.  
Also available Stainless Steel or Inconel Wire Mesh Core.

**Standard Shape:** Single Bulb-Single Tail  
Also available single bulb-double tail, double bulb  
Other configurations also available



Maxsil® Tex Tadpole Seal  
Style MTS-30-KWM/MRB


Maxsil® Tex Tadpole Seals are also available with standard 304 Stainless Steel Wire Mesh as a protective cover over the MTS-30 Silica fabric. The wire mesh is a good option for added durability. For higher temperature service the above Seal can also be manufactured with Inconel Knitted wire mesh cover.

**Standard Protective Cover:** 304SS Wire Mesh  
Also available with Inconel wire mesh.

**Standard Tadpole Cover:** Style MTS-30  
Also available with Vermiculite Coating for increased durability.

**Standard Tadpole Core:** Style Maxsil® MRB Rope.  
Also available Stainless Steel or Inconel Wire Mesh Core.

**Standard Shape:** Single Bulb-Single Tail  
Also available single bulb-double tail, double bulb  
Other configurations also available



## Overall Widths

- 1"
- 1 1/4"
- 1 1/2"
- 1 3/4"
- 2"
- 2 1/2"
- 3"

Other sizes also available upon request.

## Bulb Diameters

- 3/8"
- 1/2"
- 5/8"
- 3/4"
- 1"



## **Other Maxsil® Products Available**



**McAllister Mills, Inc.**  
800-662-9745

**173 Rainbow Circle**  
276-773-3114

**Independence, VA 24348**  
276-773-2451 Fax